

## Boards&Sheets

### Product: GF-10

Application	Boards&Sheets
Type	Lead
Content(PbO)	23.0 - 26.0%
Typical Addition	4.2 - 4.8
Lubrication	★★
Form	Flake

### Typical Formulation

Material	CPE System	ACR System
PVC K67	100	100
GF-10	4.2-4.8	4.2-4.8
CPE	8.5-10	/
Impact Modifier ACR	/	6-7
ACR Processing Aid	1-2	0.5-1.5
CaCO <sub>3</sub>	5-10	5-10

### Properties

GF-10 is an onepack stabilizer applied in extrusion of boards&sheets, profile, etc.. It greatly improves physical performance and low separation to finished products. The performance-price ratio of GF-10 is high.

GF-10 has a medium level of lubrication and is suitable to be used in a wide range of conical and parallel double screws extruder.

All raw materials and every batch of one pack are tested to a high standard to ensure product consistency and meet the high quality demands of the customer. A quality assurance certificate can be provided for each product batch according to customer's request and supported by our ISO 9001:2008 Quality management system.

### Package

3 in 1 plastic/paper bag(25kg N.W) or plastic woven container sack. Period of quality guarantee is one year.

### Storage

Stored in dry place, to avoid high temperature, kept away from sulfide.

NANJING JINLING CHEMICAL CO.,LTD.

Add:No.55, NJC Road, Chemical Industry Park Nanjing China. Post Code: 210047  
 Tel: ( 025 ) 85315451、 84712677、 84716016 Fax: ( 025 ) 85315451  
 Email: angel.cai@njchem.net Web: www.njchem.net