

Pipe Fitting

Product: PFJ 5005

Application	Injection PVC Pipe Fitting
Type	Ca Zn
Typical Addition	4.0 - 6.0
Lubrication	★★★
Form	Flake

Typical Formulation

Material	PVC Pipe Fitting
PVC K57	100
CaCO ₃	5-10
PFJ 5005	4.0-6.0
ACR Processing Aid	0.5-2.5
Pigment	As needed

Properties

PFJ 5005 is an onepack stabilizer applied in injection of PVC pipe fittings. It provides excellent processing performance to produce PVC pipe fittings with high impact strength, surface finish and overall heat stability.

PFJ 5005 is supplied in low dust flake form which should be mixed in a high speed mixer to a discharge temperature of 120 °C and in low speed mixer to a discharge temperature of 40 °C .

All raw materials and every batch of one pack are tested to a high standard to ensure product consistency and meet the high quality demands of the customer. A quality assurance certificate can be provided for each product batch according to customer's request and supported by our ISO 9001:2008 Quality management system.

Package

Valve side paper/PE bag(25kg N.W) or plastic woven container sack. Period of quality guarantee is one year.

Storage

Stored in dry place, to avoid high temperature, kept away from sulfide

NANJING JINLING CHEMICAL CO.,LTD.

Add:No.55, NJC Road, Chemical Industry Park Nanjing China. Post Code: 210047
 Tel: (025) 85315451、84712677、84716016 Fax: (025) 85315451
 Email: angel.cai@njchem.net Web: www.njchem.net